



3MP 4G Outdoor Weatherproof Bullet Camera

- 3MP (2304 x 1296) Resolution
- All Time Color Vision
- Full Duplex Audio Intercom (Built-in High Sensitivity Mic & Speaker)
- Support 10x Digital Zoom
- Area Motion Detection, Humanoid Detection, Push Real time Notification on the Application
- Mobile Notification on Human & Motion Detection
- Customized Pre-recorded Voice Alarm
- Support Micro SD Card up to 256GB & Cloud Storage(Optional)
- Compression : H.264 / H.265 / H.265+
- 4G connection. QR Code For EseeCloud to Add Camera in the App
- Monitoring : Mobile/PC Software
- Alexa Support

Specification

MODEL	PIX-IP-3IBP-256-I4G	
Image Sensor	1/2.8" CMOS Sensor	
Resolutions	3MP (2304 x 1296)	
Lens	4mm	
IR LED	4 IR Array	
IR Distance	30 Meters	
White LED	4 White Array	
White LED Distance	20 Meters	
Min Illumination	Color: 0.01 Lux, Black & White: 0.001 Lux	
Day & Night	IR-cut Auto ICR	
Light Mode	Full Color / Infrared / Intelligent	
Viewing Angle	Horizontal: 75°, Vertical: 59°, Diagonal: 88°	
Video Streaming	Main Stream: 2304 x 1296 / 15 fps	Sub Stream: 800 x 448 / 15 fps
Audio Input/Output	Two way audio, Built in microphone and speakers	
Audio Compression Standard	AAC/G711A	
Zoom	10x Digital	
DNR	3D Digital Noise Reduction	
White Balance	Auto	
WDR	D-WDR	
Mirror/Flip	On / Off	
Electronic Shutter	Auto	
On Screen Display (OSD)	Date, Time, & Title	
AI Features	Motion Detection, Human Detection.	
Privacy Zone	Support 4 Zone	

Feature	Specification
Monitoring	Andriod, iOS, Windows
Slots	4G Sim Card / Micro SD Card
Storage	Support Micro SD Card upto 256GB & Cloud Storage(Optional)
Protocol	N1/Onvif/Rtmp/Rtsp
Connection Mode	4G Sim Network / Lan Network
4G Frequency Band	FDD-LTE : B1/B3/B5/B8; TDD-LTE : B34/B38/B39/B40/B41
Button	Reset Button
Light Mode Indication	LED Blink : Not connected to Network,
Connectors	LED Continous ON : Connected to Network RJ45 LAN connector (100 Mbps) and DC Power Input
Power Input	DC : 12V/1A (DC 2.1mm Connector)
Power Consumption	≤ 6W
Working Temperature / Humadity	0-50° C RH Less than 95% (No Condensation)
Storage Temperature / Humadity	-20° C to 60° C / 20% to 90% RH
Housing Type	Plastic
Dimension	141.4mm X 69.8mm X 159mm (H x W x L)
Net Weight	205 Gms
Gross Weight	413 Gms

